

# Specifications

## Application Type

---

**Application** Signmaking  
Vehicle Marking  
Trucks  
Safety  
Public Transport

**Interior or Exterior use** Exterior

## Adhesive & Liner

---

**Adhesive** Permanent, pressure activated adhesive

**Adhesive Composition** Solvent-based acrylic

**Adhesive colour** Clear

**Adhesive Strength** 22 N/25mm

**Adhesive Type** Pressure Activated

**Adhesive Technology** 3M Controltac™

**Removability** Removable

**Material used as liner** Double sided PE coated paper

## Temperature Resistance

---

**Minimal Temperature Resistance** -34 °C

**Maximal Temperature Resistance** 93 °C

## Application Specifications

---

**Curve Format** Corrugated surfaces  
Curved surfaces  
Rivets

## Dimensions

---

**Thickness** 180 µ

## Product Storage

---

**Shelf Life** 2 years from date on original box

---

<b>Storage &amp; Transport conditions</b>	+4 - 40oC
---	-----------

### **Application Temperature**

---

<b>Minimum Application temperature</b>	10 °C
--	-------

<b>Maximum Application temperature</b>	38 °C
--	-------

### **Durability**

---

<b>Durability (range)</b>	Up to 8 years
---------------------------	---------------

### **Product Type**

---

<b>Product Type</b>	Cast
---------------------	------