

Specifications

Application Type

Application	Decoration Signmaking Car wrap
Interior or Exterior use	Exterior Interior

Adhesive & Liner

Adhesive	Grey solvent acrylic, pressure-sensitive, repositionable, air release channels
Adhesive Composition	Solvent-based acrylic
Adhesive colour	Grey
Adhesive Strength	20 N/25mm
Adhesive Type	Pressure Activated
Adhesive Technology	3M Controltac™ 3M Comply™
Removability	Permanent
Material used as liner	double-sided Polyethylene coated paper
Liner Colour	White

Temperature Resistance

Minimal Temperature Resistance	-60 °C
Maximal Temperature Resistance	107 °C

Application Specifications

Curve Format	Curved surfaces Slightly curved surface Flat surfaces Deeply Corrugated Surface
---------------------	--

Dimensions

Thickness	90 µ
------------------	------

Product Storage

Shelf Life	Use within 2 years from the date of manufacture on the sealed original box. Use within 1 year after opening the box.
-------------------	--

Storage & Transport conditions	+4°C to +40°C, out of sunlight, original container in clean and dry area.
---	---

Application Temperature

Minimum Application temperature	16 °C
--	-------

Durability

Durability (range)	Up to 6 years outdoor, 10 years indoors*
---------------------------	--

Surface Type

Surface Type	Flat surfaces Curved surfaces Rivets
---------------------	--

Product Type

Product Type	Cast
---------------------	------